

# PLC-XL50

## Ultra Short Throw Projector



### Main Features:

- ◆ Native XGA Resolution
- ◆ 2000 ANSI Lumen
- ◆ 600:1 Contrast Ratio
- ◆ Ultra Short Throw Lens (80" Image at 3" Throw Distance)
- ◆ Easy Set Up
- ◆ Digital Keystone Correction
- ◆ Integrated Audio Alarm
- ◆ Auto Input Search

Model name	PLC-XL50
Panels	0.8 inch TFT p-Si x 3
No. of pixels	2,359,296 (1024 x 768 dots)
Projection lamp	Single 275W Lamp
Brightness	2000 ANSI lumens
Contrast	600:1
Uniformity	80% (corner to centre)
Keystone Correction	Digital Keystone : ± 5° vertical
Terminal	Input 1: 1 x Dsub15 Input 2: 1 x Dsub15 (Switchable) Input 3: 3 x RCA (Component/ Composite)
Audio Out	RCA (L/R) for Video Mini-jack Stereo for Computer Input Mini-jack Stereo for Audio Out (Variable)
Communication Terminal	RS232C (Mini DIN 8 Pin)
Computer compatibility	UXGA/ SXGA+ / SXGA/ WXGA/ SVGA/ VGA/ MAC
Colour systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Scanning frequency	H/V sync ~ 15-100kHz ~ 50-100Hz, Dot clock 140 MHz
Voltage	100V-240V AC (auto voltage)
Dimensions (W x H x D)	374 x 197 x 495 mm
Weight	7.2kg

Specifications subject to change without notice

**I M E X**

Coatbridge Business Centre  
Main Street, Coatbridge, ML5 3RB

Tel: 01236 440840 Fax: 01236 449392  
E-mail: [wdgray@imex.co.uk](mailto:wdgray@imex.co.uk)  
[www.imex.co.uk](http://www.imex.co.uk)